

PS-IPCT2FB-L5ASF

2MP Fixed IR Bullet Camera



KEY FEATURES

- Metal + Plastic
- Up to 1920x1080@30fps
- S+265/H.265/H.264
- Min. illumination Color: 0.002Lux@F1.6
- Smart IR, IR Range: 50m
- Support tripwire and perimeter
- Built-in Mic, SD Card Slot, Reset Button
- Audio I/O 1/1, Alarm I/O 1/1
- Operating Conditions -35°C~65°C, 0~95% RH
- POE, IP67



Nexilis Electronics India Pvt Ltd

Email: sales@picsys.in
Website: www.picsys.in

Tel: 1800-121-123030
+91-9019706824

Camera

Image Sensor	1/2.8" CMOS
Signal System	PAL/NTSC
Min. Illumination	Color:0.02Lux@ (F1.6,AGC ON),B/W:0Lux with IR
Shutter Time	1s to 1/100,000s
Day & Night	Dual IR Cut Filter with Auto Switch
WDR	120dB
Angle Adjustment	Bracket, pan 0~360°, tilt 0~75°, rotate 0~360°

Lens

Lens type	Fixed
Focus	2.8-4mm
Lens mount	M12
Aperture Range	F1.6 Fixed
FOV	Horizontal field of view:99.7°(2.8mm)/88.3°(4mm); Vertical field of view:55.1°(2.8mm)/46.8°(4mm)

Illuminator

IR LEDs	2
IR Distance	Up to 50 m
Wavelength	850nm
White LEDs/Warmlights	N/A

Compression Standard

Video Compression	S+265/H.265/H.264
Video Bit Rate	32Kbps~6Mbps
Audio Compression	G.711A/G.711U/ADPCM_D
Audio Sampling Rate	8K,32K,48Kbps

Image

Max. Resolution	1920x1080
Mainstream	PAL:25fps(1920x1080,1280x720,704x576,640x480) NTSC:30fps(1920x1080,1280x720,704x480,640x480)
Sub Stream	PAL:25fps(704x576,704x288,640x360,352x288) NTSC:30fps (704x480,704x240,640x360,352x240)
Third Stream	N/A
Image Setting	Saturation, brightness, contrast, sharpness, adjustable by client software or web browser
Image Enhancement	BLC/3D DNR/HLC
ROI	Support 8 fixed regions of coding
OSD	16x16,32x32,48x48, adaptable size, Letters Such as Week, Date, Time, Total 1 Regions
Picture Overlay	N/A
Privacy Mask	Yes,4 regions
Smart Defog	Yes



Feature	
Alarm Trigger	Motion Detection, Mask Alarm, IP Address Conflict
Video Analytics	Tripwire, Perimeter
Early Warning (EW)	N/A
Network	
Protocols	HTTP,TCP/IP,UDP,UPnP,ICMP,DHCP,DNS,DDNS,Easy DDNS,NTP,IPv4,RTSP,RTMP
System Compatibility	ONVIF(PROFILE S/T/G),SDK,CGI,Milestone,P2P(Mutually exclusive with Profile G)
ANR	Yes (Only Support Picsys ANR NVR)
Remote Connection	2
Client	Picsys Connect, Picsys CMS
Web Version	web6
Interface	
Communication Interface	1 RJ45 10M/ 100M self-adaptive Ethernet port
Audio I/O	1/1 Mic in
Alarm I/O	1/1
Built-In Speaker	NA
Reset Button	Yes
On-board storage	Built-in Micro SD card slot, up to 512GB
General	
Protection	IP67
Web Client Language	English & 16 other languages
Operating Conditions	-35°C ~ 60°C,0 ~ 95% RH
Power Supply	DC 12V±25%, PoE(802.3af)
Power Consumption	MAX:6W(12V) MAX:8W(POE)
Heater	N/A
Package/Boundary Dimensions	160.8x68x74.5mm(6.33x2.68x2.93 inch)
Gross/Net Weight	0.47Kg(1.03lb) 0.31Kg(0.68lb)

* Listed resolutions are only selectable options. It does not mean that all streams can work at their maximum resolution at the same time.

