

# 5MP Fixed Bullet Camera

## KEY FEATURES

- Metal+Plastic
- Up to 2592x1944@20fps
- S+265/H.265/H.264
- Color: 0.002Lux@F1.6
- IR Range: 50mts
- Support tripwire and perimeter
- Built-in Mic, SD Card Slot, Reset Button
- Operating Conditions -35°C~65°C,  
0~95%RH
- POE, IP67



**PS-IPCT5FB-L5ASF**



**Nexilis Electronics India Pvt Ltd**

Email: [sales@picsys.in](mailto:sales@picsys.in)  
Website: [www.picsys.in](http://www.picsys.in)

Tel: 1800-121-123030  
+91-9019706824

### Camera

Image Sensor	1/2.8" CMOS
Signal System	PAL/NTSC
Min. Illumination	Color:0.02Lux@ (F1.6,AGC ON),B/W:0Lux with IR
Shutter Time	1s to 1/100,000s
Day & Night	Dual IR Cut Filter with Auto Switch
WDR	120dB
Angle Adjustment	pan 0~340°,tilt 0~75°,roate 0~360°

### Illuminator

IR LEDs	2
IR Distance	Up to 50 m
Wavelength	850nm
White LEDs/Warmlights	N/A

### Compression Standard

Video Compression	S+265/H.265/H.264
Video Bit Rate	32Kbps~6Mbps
Audio Compression	G.711A/G.711U/ADPCM_D
Audio Sampling Rate	8K,32K,48Kbps

### Lens

Lens type	Fixed
Focus	4mm
Lens mount	M12
Aperture Range	F1.6 Fixed
FOV	Horizontal field of view:94.7°(2.8mm)/80°(4mm) ; Vertical field of view:71.2°(2.8mm)/58.1°(4mm)

### Image

Max. Resolution	2592x1944
Mainstream	PAL:20fps(2592x1944,2592x1520),25fps(2560x1440,2304x1296,1920x1080,1280x720) NTSC:30fps(2592x1944,2592x1520),25fps(2560x1440),30fps(2304x1296,1920x1080,1280x720))
Sub Stream	PAL:20fps(704x576,704x288,640x360,352x288) NTSC:30fps(704x480,704x240,640x360,352x240)
Third Stream	NA
Image Setting	Saturation, brightness, contrast, sharpness, adjustable by client software or web browser
Image Enhancement	BLC/3D DNR/HLC
ROI	NA
OSD	16x16,32x32,48x48, adaptable size, Letters Such as Week, Date, Time, Total 5 Regions
Picture Overlay	N/A
Privacy Mask	Yes,4 regions
Smart Defog	Yes

Feature	
Alarm Trigger	Motion Detection, Mask Alarm, IP Address Conflict
Video Analytics	Tripwire, Perimeter
Early Warning (EW)	N/A
Network	
Protocols	HTTP, TCP/IP, UDP, UPnP, ICMP, DHCP, DNS, DDNS, Easy DDNS, NTP, IPv4, RTSP, RTMP
System Compatibility	ONVIF (PROFILE S/T/G), SDK, CGI, Milestone, P2P (Mutually exclusive with Profile G)
ANR	Yes (Only Support Picsys ANR NVR)
Remote Connection	2
Client	Picsys Connect, Picsys CMS
Web Version	web6
Interface	
Communication Interface	1 RJ45 10M/ 100M self-adaptive Ethernet port
Audio I/O	Mic in
Alarm I/O	NA
Built-In Speaker	NA
Reset Button	Yes
On-board storage	Built-in Micro SD card slot, up to 512GB
General	
Protection	IP67
Web Client Language	English & 16 other languages
Operating Conditions	-35°C ~ 60°C, 0 ~ 95% RH
Power Supply	DC 12V±25%, PoE(802.3af)
Power Consumption	MAX:6W(12V) MAX:8W(POE)
Heater	N/A
Package/Boundary Dimensions	116.6x83.7mm(4.59x3.30inch)
Gross/Net Weight	0.47KG 0.3kg

\* Listed resolutions are only selectable options. It does not mean that all streams can work at their maximum resolution at the same time.

