

5MP Motorized Bullet Camera



- **Key Features:**
- Metal Housing
- Motorized Lens 2.7-13.5mm
- Up to 2880x1620@30fps, 1920x1080@60fps
- S+265/H.265/H.264
- IR, IR Range: 80m
- Support tripwire and perimeter
- Built-in Mic, SD Card Slot, Reset Button
- Audio I/O 1/1, Alarm I/O 1/1
- POE, IP67
- Support Human/Vehicle Classification
- Support Face Capture Mode

PS-IPCT5MB-L8ASF



Nexilis Electronics India Pvt Ltd

Email: sales@picsys.in
Website: www.picsys.in

Tel: 1800-121-123030
+91-9019706824

OPERATIONAL	
Signal System	PAL/NTSC
Image Sensor	1/2.8" CMOS
Day and Night	Auto
WDR	120db
Angle Adjustment	Bracket, pan 0~360°, tilt 0~75°, rotate 0~360°
Min. illumination (Color / B / W)	Colour: 0.002Lux@ (F1.6, AGC ON), B/W: 0Lux with IR
Focal Length	2.7-13.5mm
Lens mount	14
Lens Type	Motorized
Aperture	F1.6-F3.3 Fixed
Angle of View (FOV)	Horizontal field of view: 94.2° ~ 29.3°
Electronic Shutter Speed	1s to 1/100,000s
IR Distance	Up to 80m
IR Led	4
Wavelength	850nm

White/warm LEDs	NA
Backlight Compensation (BLC)	3D
DNR/HLC	Yes
Image setting	Saturation, brightness, contrast, sharpness, adjustable, by client software or web browser
OSD	16x16x, 24x24, 32x32, 48x48, 64x64, adaptable size, letters such as week, date, time etc
Privacy Masking	Yes
Defog	Yes
On board storage	Built In micro sd card slot, upto 512 Gb
Reset Button	yes
Alarm I/O	2/1

VIDEO	
Video Compression	S+265/H.265/H.264
Resolution	5MP (2592x1944) PAL:
Frame Rate Main Stream	25fps(2880x1620, 2688x1520, 2560x1440, 2304x1296) 50fps (1920x1080, 1280x720)) NTS 30fps (2880x1620, 2688x1520, 2560x1440, 2304x1296) 60fps (1920x1080, 1280x720)
Frame Rate Second Stream	PAL: 25fps(704x576, 704x288, 640x360, 352x288) NTSC: 30fps(704x480, 704x240, 640x360, 352x240)
Frame Rate Third Stream	PAL: 25fps(1920x1080, 1280x720, 704x576, 704x288, 640x360, 352x288) NTSC: 30fps(1920x1080, 1280x720, 704x480, 704x240, 640x360, 352x240)
Bit Rate	32kbps-6mbps
Audio	
Audio Compression	G.711/G.711U/ADPCM
Audio I/O	1/1 Mic In

Audio Interface	1 RJ45 10M/ 100M self adaptive Ethernet port
Audio Sampling Rate	8K/48Kbps
Feature	
Alarm Trigger	Event Input, Event Output, Motion Detection, Mask Alarm, Disk Full, Disk R/W Error, IP Address, Conflict, MAC Address Conflict, FTP Server Exception, Voltage Abnormal
Video Analytics	Tripwire, Double Tripwire, Perimeter, Object Abandon, Object Lost, Loitering, Running, Parking, Crowded, People Counting, On Duty Detection, Video Abnormal, Audio Abnormal, Heatmap, Face Capture (Face Detection), Safety Helmet Detection, Human/
Early Warning	NA
NETWORK	
Ethernet	Self adaptive
Supported Web Browsers	Web
Protocols*	TCP/IP, ICMP, HTTP, HTTPS, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, MULTICAST, UPnP, FTP, IPV4, NTP, SMTP, IGMP, 802.1x, QoS, IPV6, ARP, UDP, SNMP, SSL, Telnet, SNT, RTMP, SFTP, NFS
APP	PICSYS Connect
System compatibility	ONVIF (PROFILE S/T/G), SDK, Milestone, CGI, P2P
Protection	IP67, Lightning protection, surge protection and voltage transient protection meets EN 55035:2017
Remote Connection	≤7
Languages Supported	English/Thai/French/Polish/Dutch/German/Arabic
ELECTRICAL	
Power Supply	DC12V±25%/PoE
Power Consumption	MAX: 8.5W (12V) MAX: 10W (PoE)
MECHANICAL	
Dimensions (D x D x H)	264.3 x95x 83.2mm
Product Weight	1.15kg
ENVIRONMENTAL	
Operating Temperature	-35 ~65 , 0~95% RH

* Listed resolutions are only selectable options. It does not mean that all streams can work at their maximum resolution at the same time.



Nexilis Electronics India Pvt Ltd

Email: sales@picsys.in
 Website: www.picsys.in

Tel: 1800-121-123030
 +91-9019706824