

5MP Motorized Dome Camera



PS-IPCT5MD-L3ASF

KEY FEATURES

- Housing: Full Metal
- 2.7-13.5mm Motorized Lens
- Up to 2592x1944@20fps
- S+265/H.265/H.264
- Color: 0.002Lux@F1.6

·Support

- 120dB WDR
- Smart IR, IR Range: 30m
- Support tripwire and perimeter
- Built-in Mic, SD Card Slot, Reset Button
- Operating Conditions -40°C~60°C, 0~95% RH
- POE, IP67, IK10



Nexilis Electronics India Pvt Ltd

Email: sales@picsys.in
Website: www.picsys.in

Tel: 1800-121-123030
+91-9019706824

Camera	
Image Sensor	1/2.8" CMOS
Signal System	PAL/NTSC
Min. Illumination	Color:0.02Lux@(F1.6,AGC ON),B/W:0Lux with IR
Shutter Time	1s to 1/100,000s
Day & Night	Dual IR Cut Filter with Auto Switch
WDR	120db
Angle Adjustment	pan 0~330°,tilt 0~75°,roate 0~350
Lens	
Lens type	Motorized
Focus	2.7-13.5mm
Lens mount	Φ14
Aperture Range	F1.6
FOV	Horizontal field of view:96.4°~31.4 ; Vertical field of view:53.5~17.7°
Illuminator	
IR LEDs	18
IR Distance	Up to 30 m
Wavelength	850nm
White LEDs	N/A
Compression Standard	
Video Compression	S+265/H.265/H.264
Video Bit Rate	32Kbps~6Mbps
Audio Compression	G.711A/G.711U/ADPCM_D
Audio Sampling Rate	8K,32K,48Kbps
Image	
Max. Resolution	2592x1944
Mainstream	PAL:25fps(1920x1080,1280x720,704x576,640x480) NTSC:30fps(1920x1080,1280x720,704x480,640x480)
Sub Stream	PAL:25fps(704x576,704x288,640x360,352x288) NTSC:30fps (704x480,704x240,640x360,352x240)
Third Stream	NA
Image Setting	Saturation, brightness, contrast, sharpness, adjustable by client software or web browser
Image Enhancement	BLC/3D DNR/HLC
ROI	NA
OSD	16x16,32x32,48x48, adaptable size, Letters Such as Week, Date, Time, Total 1 Regions
Picture Overlay	NA
Privacy Mask	Yes,4 regions
Smart Defog	Yes

Feature	
Alarm Trigger	Motion Detection,Mask Alarm,IP Address Conflict
Video Analytics	Tripwire,Perimeter
Early Warning (EW)	NA
Network	
Protocols	HTTP, TCP/IP,ICMP,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,UPnP,UDP
System Compatibility	Milestone, P2P (Mutually exclusive with Profile G) ONVIF (PROFILE S/T/G), SDK, CGI, Yes (Only Support Picsys ANR NVR)
ANR	
Remote Connection	2
Client	Picsys Connect, Picsys CMS
Web Version	web6
Interface	
Communication Interface	1 RJ45 10M/ 100M self-adaptive Ethernet port
Audio I/O	Mic in
Alarm I/O	NA
Built-In Speaker	NA
Reset Button	Yes
On-board storage	Built-in Micro SD card slot, up to 512GB
General	
Protection	IP67
Web Client Language	16 languages Russian/ Thai/ French/ Polish/ Dutch/ Hebraism/ Farsi/Arabic/ Vietnamese
Operating Conditions	-35°C ~ 60°C,0 ~ 95% RH
Power Supply	DC 12V±25%, PoE(802.3af)
Power Consumption	MAX:6W(12V) MAX:8W(POE)
Heater	N/A
Package/Boundary Dimensions	Φ143x124mm(Φ5.63x4.88inch)
Gross/Net Weight	0.86Kg(1.90lb), 0.86Kg(1.90lb)

the same time.

* Listed resolutions are only selectable options. It does not mean that all streams can work at their maximum resolution at

